

HEAVY DUTY



PolarTech PT-PROi

- ◆ LOW OPERATING COSTS
- ◆ NO USE OF WATER
- ◆ DRY ICE
- ◆ NON TOXIC
- ◆ EASY TO OPERATE
- ◆ HIGH POWER PRESSURE



POLARTECH.




POLARTECH PT-PROi



TECHNICAL DATA:

| | |
|-----------------------|--|
| Dimension W x D x H: | 650 x 550 x 950 mm |
| Weight: | 70 kg |
| Air flow range: | 0.8 -9 m ³ /min. |
| Blast pressure range: | 2-14 bar |
| Tank capacity: | 25 kg |
| Pellet consumption: | 0 – 75 kg/hour (variable) |
| Power supply: | 110V-230V / AC 50-60 Hz |
| Air quality: | Dry and free of oil and particles |
| Noise: | 60-120 dB (A) depending on nozzle and pressure |

STANDARD EQUIPMENT:

-  Adjustment of air pressure
-  Adjustment of pellet consumption
-  Safety switch

| | |
|------------------|--|
| Blasting gun: | · Ice/Granulate |
| Blasting hose: | · 5 m 3/4" incl. quick safety coupling · Electrical connection · Protective sleeve |
| Air supply hose: | 10 m 3/4" incl. claw coupling |
| Electrical cord: | 10 m |
| Nozzle: | Ø7 mm Standard plastic round <i>Standard round nozzle (customer choice)</i> |

OPTIONAL:

- Wide range of round, flat and bended nozzles
- Wide range of special nozzles



POLARTECH.